



S-8180T - 8 Port Gigabit Ethernet Switch

Product Highlights

- 1.9 Million packets/second forwarding rate
- Up to 16 Gbit/s switching capacity
- Up to 4,000 MAC Addresses
- SysKonnnect SK-8T08 compatible

Features

- 8 Ports 10/100/1000Base-T, Auto MDI/MDI-X Auto-negotiation
- 128 KB packet buffer memory
- 2 priority queues per port
- Honors 802.1p values and honor IP DSCP values
- Weighted Round Robin (WRR) scheduling across queues
- 1U, desktop, Wall- or rack-mounting

Standard Compliances

- IEEE 802.3 10/100/1000Base-T
- IEEE 802.3x with Flow control / Auto-negotiation
- IEEE 802.1p Quality of Service
- IEEE 802.3ab Gigabit Ethernet standards

Safety Standards

- CAN/CSA-C22.2 No. 60950-1:2007, CB, CE, TÜV, UL 60950-1:2007

EMC

- CE Class A, FCC Class B

Environmental Specifications

- Storage: -20° to 70°C (-4° to 158°F), 10% to 95% Relative Humidity (non-condensing)
- Operating: 0° to 40°C (-32° to 104°F), 10% to 90% Relative Humidity (non-condensing)



S-8180T - 8 Port Gigabit Ethernet Switch

RoHS, other

- RoHS compliant

Dimension

- 44x266x162 mm, 1.7x10.5x6.4" (High, Width, Deep)

Weight

- Unit 1,45 kg, packet 2,35 kg

Warranty

- 2 Years

Order numbers

- 100-001-001-008

© Copyright 2009 S2Konnnect

All rights reserved. All brand and product names are trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.

Germany

S2Konnnect GmbH
Siemensstrasse 23
D-76275 Ettlingen
Phone: +49 7243 3435725
Fax: +49 7243 3435723
E-mail: sales@s2konnnect.de

www.s2konnnect.com